Simple and easy appearance, in line with contemporary aesthetic concept. The product has the structure and appearance design patent. The lamp body adopts high-pressure cast aluminum and aluminum alloy, the surface is coated with outdoor used powder , double anti-corrosion to extend service life. This lawn lamp series uses LED. High efficiency constant current driver, ensure the light source is maximum used.

FIELDS OF APPLICATION
Office & Education, offices, open-plan offices, conference rooms, conference rooms, reception areas, counters, galleries, hotels, restaurants, living spaces

IEC 62717 LED-modules for general lighting – Performance requirements
IEC 62722-2-1 Particular requirements for LED luminaires

High Lumen Efficacy 115lm/W
Body - Die cast aluminum housing with solvent free powder coating
Diffuser - PMMA polycarbonate pattern lens.
Glowing Wire Test - 850°
Temperature - ta=20 °C ~ ta max=50 °C
Class - III

Model --- **FURAT1**

7 years Guarantee **Standard Guarantee**

Default Available

FURAT1-A-0-15-27-W-6W-IP20

Product Assistant Chart

FURAT1 X X X X X

Size: A B C

Driver: 0 On/Off | 1 Dali | 2 Dimmable | 3 Phase Dimming | 4 1-10 | 5 0-10

Beam Angle: 15° 24° 36° 36°

Kelvin: 27 2700K | 30 3000K | 40 4000K | 50 5000K | 60 6000K | RGBW | TUN

Finishing: W white | B black

Wattage: 4W 6W 8W 10W 12W 15W 18W 20W



A - Ø105-80mm
B - Ø105-92mm
C - Ø105-110mm
D - Ø105-125mm



Lighting Customization Solution can offer you modifications for environment with higher options as a customized product.

IP-20
IP-44

COB

McA Step 3

220~240V

LIGHTING SOLUTIONS
TRIDONIC





LED life time			Operating time 1.000 h									
Lamp Lumen Maintenance Factor			1	10	20	30	40	50	60	70	80	90	100
Lamp Survival Factor			1	1	1	1	1	1	1	1	0.99	0.99	0.99
L80	50.000 h	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.64	0.60
		LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.99	0.98
L80	100.000 h	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82	0.80
		LSF	1	1	1	1	1	1	1	0.99	0.99	0.99	0.99

A++ ENERGY LEVEL | LED | CRI>90 | series wiring | F | CE | UV | LM-80 | FLICKER FREE