Simple and easy appearance, in line with contemporary aesthetic concept. The product has the structure and appearance design patent. The lamp body adopts high-pressure cast aluminum and aluminum alloy, the surface is coated with outdoor used powder , double anti-corrosion to extend service life. This lawn lamp series uses LED. High efficiency constant current driver, ensure the light source is maximum used.

FIELDS OF APPLICATION
Office & Education, offices, open-plan offices, conference rooms, conference rooms, reception areas, counters, galleries, hotels, restaurants, living spaces

IEC 62717 LED-modules for general lighting – Performance requirements
IEC 62722-2-1 Particular requirements for LED luminaires

Model ---ZETA-RO Trimless Recessed Light

7 years Guarantee **Standard Guarantee**



Default Available

ZETA-A-0-15-27-W-4W-IP20

Product Assistant Chart

ZETA XXXXX

- Size: A B C D
- Driver: 0 On/Off; 1 Dali; 2 Dimmable; 3 Phase Dimming; 4 1-10; 5 0-10
- Beam Angle: 15° 24° 36° 36°
- Kelvin: 27 2700K; 30 3000K; 40 4000K; 50 5000K; 60 6000K; RGBW; TUN
- Finishing: W white; B black
- Wattage: 4W 6W 8W 10W 12W 15W 18W 20W

A - Ø95-74mm
B - Ø95-76mm
C - Ø95-94mm
D - Ø95-109mm



Lighting Customization Solution can offer you modifications for environment with higher options as a customized product.

IP-20
IP-44

COB

McA Step 3

220~240V

LIGHTING SOLUTIONS
TRIDONIC





LED life time			Operating time 1.000 h									
Lamp Lumen Maintenance Factor			1	10	20	30	40	50	60	70	80	90	100
Lamp Survival Factor			1	1	1	1	1	1	1	1	0.99	0.99	0.99
L80	50.000 h	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.64	0.60
		LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.99	0.98
L80	100.000 h	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82	0.80
		LSF	1	1	1	1	1	1	1	0.99	0.99	0.99	0.99

A++ ENERGY LEVEL | LED | CRI>90 | series wiring | F | CE | UV | LM-80 | FLICKER FREE